



# Armour Fire Safety Inc.

**MULTI-PURPOSE ABC DRY CHEMICAL**

**BUILT TOUGH AND EASY TO SERVICE**

**STRIKE FIRST ABC MULTI-PURPOSE DRY CHEMICAL  
FIRE EXTINGUISHERS ARE DESIGNED FOR:**



**CLASS A**

**WOOD,  
PAPER,  
CLOTH**



**CLASS B**

**FLAMMABLE  
LIQUIDS  
& GASES**



**CLASS C**

**ELECTRICAL  
CONDUCTIVITY**



**6 YEAR  
WARRANTY**

- Steel cylinder complete with protective skirt
- Super durable polyester powder paint finish with superior corrosion resistance
- Waterproof stainless steel gauge
- Handle reinforced, full grip hardcoat anodized aluminum
- Oversized pull pin with retaining strap for easier and faster activation
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- U.S.C.G. approved with bracket listed on label
- Temperature range: -65°F to 120°F (-54°C to 49°C)



**LISTED**

MEETS OR EXCEEDS:  
ANSI/UL 299 & 711



**LISTED  
HOMOLOGUÉ**

MEETS OR EXCEEDS:  
CAN/ULC-S504 & S508

CAPACITY	2.5 lbs.	5 lbs.	5 lbs.	10 lbs.	20 lbs.	30 lbs.
Model No.	SF-ABC110ST	SF-ABC310	SF-ABC340	SF-ABC680	SF-ABC1020	SF-ABC30
Part No.	ABC-025VWD	ABC-050WWD	ABC-050WWDL	ABC-100WWD	ABC-200WWD	ABC-300WWD
UL/ULC Rating	1-A : 10-B : C	3-A : 10-B : C	3-A : 40-B : C	6-A : 80-B : C	10-A : 120-B : C	10-A : 120-B : C
U.S.C.G. Approval	Type B:C Size I	Type A Size II, Type B:C Size I	Type A Size II, Type B:C Size I	Type A Size II, Type B:C Size II	Type A Size II, Type B:C Size III	Type A Size II, Type B:C Size IV
Range	8-10 ft (2.5-3 m)	8-10 ft (2.5-3 m)	8-10 ft (2.5-3 m)	10-15 ft (3-4.5 m)	10-15 ft (3-4.5 m)	10-15 ft (3-4.5 m)
Discharge Time	9 sec	13 sec	9 sec	9 sec	9 sec	9 sec
PSI	150	195	195	235	235	195
Height	15 1/4" (39 cm)	15 1/4" (39 cm)	16 7/8" (43 cm)	21 1/4" (54 cm)	24" (61 cm)	30 3/4" (78 cm)
Width	3 3/4" (9.5 cm)	6 3/4" (17 cm)	6 3/4" (17 cm)	8" (20.3 cm)	9 1/2" (24 cm)	9 1/2" (24 cm)
Diameter	3 1/8" (8 cm)	4 1/4" (11 cm)	4 1/4" (11 cm)	5 1/8" (13 cm)	7 1/8" (18 cm)	7 1/8" (18 cm)
Weight	4 1/2 lb (2 kg)	10 1/2 lb (4.8 kg)	10 1/2 lb (4.8 kg)	19 1/4 lb (8.8 kg)	35 1/4 lb (16.1 kg)	50 1/3 lb (22.8 kg)
Chrome Option	Yes	-	Yes	-	-	-
Standard Bracket	Vehicle/Marine	Wall or Vehicle/Marine	Wall or Vehicle/Marine	Wall	Wall	Wall
Optional Brackets Wall	Wall UP2-DB	UB-5DB UB-5MD HDVB-1	UB-5DB UB-5MD HDVB-1	UP-10MD HDVB-2	HDVB-3	HDVB-4 HD-CART

16708-113 Ave NW  
Edmonton, AB 2X3  
www.ArmourFireSafety.com

**ARMOUR**  
FIRE SAFETY